

Diversey

## SKY® 7Xi Disinfection Technology

iPad®\*, Tablet PC  
And Smartphone  
Disinfection  
With UVC  
Light



SKY® 7Xi is a compact unit that disinfects iPads, tablet PC's and smartphones in as little as 30 seconds using the power of UVC light.

### Features

- User-friendly operation promotes frequent disinfection of facility-owned and personal devices
- Devices disinfected without harm to a 3-log to 6-log reduction (99.9% to 99.9999% reduction\*\*) in harmful pathogens such as MRSA, VRE, MDR-Gram negative, Norovirus and *C. diff* spores
- Based upon the versatile design, the SKY® 7Xi model can be placed in multiple locations, including desk top, wall mount and mobile cart options

### Benefits

- Fast and easy to use. No mess or fumes
- Safe and effective – accommodates most mobile devices
- Nontoxic – Accessible – Small footprint and robust construction enable placement in almost any location
- Cost Effective – Low operating cost, low maintenance

### Application

- Suited for iPads, tablet PC's and smartphones up to 1" (2.54 cm) thick by 8" (20.32 cm) wide and 12" (30.5 cm) long

\* iPad® is a registered trademark of Apple (Cupertino, CA)

\*\*All results based on independent testing. *C.difficile* was tested directly and, for safety and equivalence, challenge organisms of greater irradiation resistance replaced other pathogens noted. Tests conducted with *Pseudomonas aeruginosa*, *Staphylococcus aureus* and *Bacillus atrophaeus*. Individual results may vary. Results on file.



# SKY® 7Xi Disinfection Technology

## iPad®, Tablet PC And Smartphone Disinfection With UVC Light



### Product Specifications

Description	SKY® 7Xi
Warm up time:	</= 20 seconds
Cycle time:	</= 30 seconds/1 min. Max defense mode
Power Consumption:	</= 75 Watts, 70 watts idle Standby mode after 1 hour idle (<8 watts)
Device Size:	14.125" x 23.125" x 14" (35.88 cm x 60.64 cm x 35.56 cm)
Device Weight:	44 lbs. (20 kg)
Chemical Usage:	None
Environmental:	No ozone generation
Acoustic Noise:	</= 35 db
Power:	100-120V~, 1.6A, 50/60Hz 200-240V~, 1.2A, 50/60Hz
Regulatory:	This product is in conformity with the requirements of EC Council directive MDD93/42/EEC and satisfies emission/immunity Class B limits of IEC 60601-1-2. It also conforms to Electrical Safety UL 61010-1, IEC 61010-2-040, and Certified to CAN/CSA C22.2 Nos. 61010-1 & 61010-2-040.

### SKY® 7Xi Device Components

Product Code	Description	Details
SKY-7Xi	SKY® 7Xi Mobile Device Disinfection Unit	Mobile Device Disinfection Unit
DMHD7013MRI	SKY® 7Xi Portability Cart	Attachment for Portable Rolling Applications
SKY-CARTRIDGE	SKY® Cartridge	Replaceable UVC Cartridge for Unit

Ask about our Return to Factory Warranties available for up to 5 years. Contact your Diversey Care Sales Representative.

### Replacement Parts (Available from Plan B, Inc.)

Product Code	Description
SP-00685	SKY® 7Xi, Fuse (North America)
SP-00690	SKY® Software Kit, Operating Software, V3.2.1