

Mötsenböcker's Lift Off, Inc. P.O. Box 90947 San Diego, CA 92169 Phone: 858-581-0222



Safety Data Sheet

1. Product And Company Identification

| Product Name: Product Code: Product Reference Number: | Mötsenböcker's Lift Off #1 Food, Drink and Pet Stain Remover MLO1SDS NJTSRN: 405-01, 405-02, 405-03, 405-20, 406-01, 406-55, 415-01, 421-01 | | SCScertified |
|---|---|----------------------------|-------------------------------|
| Responsible Party: | Mötsenböcker's Lift Off, Inc. P.O. Box 90947 San Diego, CA 92169 | | |
| Information Phone Number: Fax: Website: | 1-858-581-0222 1-858-483-6965 www.liftoffinc.com | 1-800-346-1633 (Toll Free) | NOC COMPLEX LOW OR NO VOCS |
| 24 Hour Emergency Phone N | umber: INFOTRAC@ 800-535-5053 | | OC COMP. |
| SDS Date Of Preparation: | 02/09/2015 | | STRESAU |

ition: Product Use and Uses Advised Against: Food, Pet, and Beverage Stain Remover



2. Hazards Identification

Note: This product is a consumer product and is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.

Note: This product has been tested for sustained combustibility by Stresau Laboratory, Inc. Due to the nature of the product, it does not Sustain combustibility. It will not start a fire from sparks. Due its water-based composition, this product is capable of stopping a fire.

GHS Classification:



| Physical: | Health: |
|-----------------------------|---------------------------|
| Flammable Liquid Category 0 | Eye Irritation Category 1 |

GHS Label Elements:



WARNING! Contains Acetone.

Statements of Hazard

Non-Flammable liquid and vapor

Prevention

Keep away from heat, sparks, open flames, hot surfaces. Keep container tightly closed. Wash exposed skin thoroughly after handling. Wear eve protection.

Storage Store in a well-ventilated place. Keep cool.

STRESAU LABORATORY, INC

Response

IF IN EYES: Rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF ON SKIN (or hair): Rinse skin with water or shower. May be a eye and skin irritant.

Disposal

Dispose of contents and container in accordance with local and national regulations.

3. Composition/Information On Ingredients*

| Component | CAS No. | Amount |
|-----------------|----------|--------|
| Acetone | 67-64-1 | 1-8% |
| Glycol Ether DB | 112-34-5 | 1-8% |
| Glycol Ether EB | 111-76-2 | 1-5% |

*There are other components in the product composition. The exact concentrations are a trade secret, proprietary and patent pending.

4. First Aid Measures

Inhalation: If inhaled, remove to fresh air. Prolonged exposure to product may cause dizziness.

Skin Contact: Contact with product can dry and 'defat' skin, causing irritation or dermatitis. Wash skin thoroughly with soap and water. Get medical attention if irritation develops or persists. Launder clothing before re-use.

Eye Contact: May cause eye irritation. If contact occurs, immediately flush eyes with large quantities of water for 15 minutes, holding the eyelids apart. Get medical attention if irritation persists.

Ingestion: If swallowed, do not induce vomiting, may cause stomach distress. Rinse mouth with water. Get medical assistance by calling a doctor or poison center. Never give anything by mouth to a person who is unconscious or drowsy.

Most Important Symptoms: Causes eye irritation. May cause minor skin irritation. Inhalation of mists may cause respiratory irritation. Inhalation of vapors may cause dizziness and headache.

Indication of Immediate Medical Attention/Special Treatment: Immediate medical attention should not be required with normal use.

5. Firefighting Measures

Suitable (and Unsuitable) Extinguishing Media: Use media suitable for surrounding fire. Cool fire exposed containers with water.

Specific Hazards Arising from the Chemical: While this product is classified as a flammable liquid under OSHA regulations, it does not sustain combustion when tested in accordance with 49CFR, Part 173, Appendix H. Stesau Laboratory, Inc. has tested this product for sustained combustibility. Due to the nature of the product, it does not sustain combustibility. It will not start a fire from sparks. Due to its water-based composition, this product is capable of stopping a fire.

Special Protective Equipment and Precautions for Fire-fighters: Firefighters should wear positive pressure selfcontained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures: Evacuate spill area and keep unprotected personnel away. Eliminate all ignition sources and ventilate the area. Wear appropriate protective clothing and equipment as described in Section 8.

Methods for Containment and Clean-Up: Stop spill at the source if it is safe to do so. Absorb with an inert material. Collect into a suitable container for disposal. Rinse area with water. Prevent entry in storm sewers and waterways. Report spill as required by local and national regulations.

7. Handling and Storage

Precautions for Safe Handling: Avoid eye and skin contact. Avoid breathing mists or vapors. Use only with adequate ventilation. Keep containers closed when not in use.

Empty containers retain product residue and may be hazardous

Conditions for Safe Storage, Including Any Incompatibilities:

Protect containers from physical damage. Store in a cool, well-ventilated area away from acids and other incompatible materials. Keep out of the reach of children.

8. Exposure Controls / Personal Protection

Exposure Guidelines:

| CHEMICAL | EXPOSURE LIMIT | |
|--|---|--|
| Acetone | 500 ppm TWA, 750 ppm STEL ACGIH TLV | |
| (The EPA has classified acetone as a non- toxic chemical and a non-VOC component.) | 1000 ppm TWA OSHA PEL | |
| Glycol Ether DB | 10 ppm TWA ACGIH TLV (Inhalable fraction and vapor) | |

Engineering Controls: General ventilation should be adequate for all normal use.

Personal Protective Equipment

Respiratory Protection: None required under normal use conditions. For operations where exposure limits may be

exceeded use a NIOSH approved respirator (mask). Selection of respiratory protection depends on the contaminant type, form and concentration. Select in accordance with OSHA 1910.134, and all other applicable regulations; and good Industrial Hygiene practice.

Gloves: None required under normal use conditions.

Eye Protection: Safety goggles are recommended if eye contact is possible.

Other Protective Equipment/Clothing: None required under normal use conditions.

9. Physical and Chemical Properties

Appearance and Odor: Clear liquid with mild fruity odor.

| Physical State: Liquid | Odor Threshold: Not determined | |
|---|--|--|
| pH: 9 – 10 | Specific Gravity: 1.0 | |
| Initial Boiling Point/Range: 199°F (93°C) | Vapor Pressure: Not determined | |
| Melting/Freezing Point: Not determined | Vapor Density: Greater than air. | |
| Solubility In Water: Complete | Percent Volatile: >80% | |
| Viscosity: Not determined | Evaporation Rate: Not determined | |
| Coefficient Of Water/Oil Distribution: Not determined | VOC Content: 3.0% (30 g/l) | |
| Flash Point: 76°F (23.8°C) <mark>*</mark> | Autoignition Temp: Not determined | |
| Decomposition Temperature: Not determined | Flammability Limits: LEL: Not determined | |
| | UEL: Not determined | |
| Flammability (solid, gas): Not applicable | | |



*See Section 5

10. Stability and Reactivity

Reactivity: Not normally reactive
Chemical Stability: Stable.
Possibility of Hazardous Reactions: Will react with acids and strong oxidizing agents.
Conditions To Avoid: Not currently known.
Incompatible Materials: Acids and strong oxidizing agents.
Hazardous Decomposition Products: Thermal decomposition will generate oxides of carbon.

11. Toxicological Information

POTENTIAL HEALTH EFFECTS:

Acute Hazards:

Inhalation: Mist and vapors may cause mild irritation of mucous membranes and upper respiratory tract.

Skin Contact: May cause minor irritation.

Eye Contact: Causes eye irritation.

Ingestion: Swallowing may cause gastrointestinal upset and nausea.

Chronic Hazards: None currently known.

Carcinogenicity Listing: None of the components is listed as a carcinogen or potential carcinogen by IARC, NTP, ACGIH or OSHA.

Acute Toxicity Values:

Acetone: LD50: Oral Rat 5,800 mg/kg, LD50: Skin Rabbit >7,426 mg/kg, LC50: Inhalation Rat 76 mg/L/ 4 hr.

Glycol Ether DB: LD50: Oral Rat 4,500 mg/kg; LD50: Skin Rabbit 4,120 mg/kg

12. Ecological Information

Ecotoxicity:

Acetone: LC50 Rainbow trout - 5540 mg/L/96 hr. EC50 Daphnia pulex - 8800 mg/L/48 hr.

Glycol Ether DB:

LC50 Lepomis marcochirus 1,300 mg/L/96 hr. EC50 Daphnia magna: 3,200 mg/L/24 hr.

Persistence and Degradability: This product has been tested and certified biodegradable by Scientific Certification Systems.

Bio accumulative Potential:Acetone:BCF = 3Glycol Ether DB:Not expected.Mobility in Soil:No data availableOther Adverse Effects:No data available



13. Disposal Considerations

Dispose of in accordance with all local, state/provincial and federal regulations. Offer empty containers for recycling.

14. Transport Information

DOT Hazardous Materials Description: Not Regulated

Canadian TDG Hazardous Materials Description: Not Regulated

IMDG Dangerous Goods Description: Not Regulated

15. Regulatory Information


United States:

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CERCLA Section 103: This product has a RQ of 50,000 lbs. based on the RQ for Acetone of 5,000 lbs present at 10.0% maximum. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Not currently known.

SARA 313: Not currently known. This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): Glycol Ether @ 2 – 10%



REVISION SUMMARY:

February 09, 2015 Update to OSHA HazCom 2012 / GHS SDS format: Changes to all sections.

March 11, 2009: Revision update. January 01, 2006: Revision update.

Prepare by: Industrial Health & Safety Consultants, Inc.

The above information is believed to be correct with respect to the formula used to manufacture the product. As data, standards and regulations change, and the conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.

CONSUMER LABELING

What is a consumer product?

OSHA Description:

• Any consumer product or hazardous substance, as those terms are defined in the Consumer Product Safety Act (15 U.S.C. 2051 et seq.) and Federal Hazardous Substances Act (15 U.S.C. 1261 et seq.) respectively.

Consumer Product Safety Commission:

• A product brought into or around a dwelling and related buildings (garages, sheds, etc.). Does not include industrial supplies – labeled as and marketed solely for industrial use.

• Includes products designed primarily for professional use but available to consumers in retail stores for non-professional use.

Who governs consumer product labeling?

OSHA exempts consumer products from labeling under OSHA.

• Any consumer product or hazardous substance as those terms are defined in the Consumer Product Safety Act (15 U.S.C. 205 et seq.) and Federal Hazardous Substances Act (15 U.S.C. 1261 et seq.) respectively, when subject to a consumer product safety standard or labeling requirement of those Acts, or regulations issued under those Acts by the Consumer Product Safety Commission

OSHA fully exempts consumer products from Hazard Communication if used in the workplace in a consumer manner.

• The Consumer Product Safety Commission (CPSC) mandates labeling for all hazardous substances that are consumer products.

• If products are sold retail and available for use around the home, they must be labeled per the CPSC.

• OSHA does require a SDS to inform workers of hazards.

This information was provided by Industrial Health & Safety Consultants, Inc. of Shelton, CT.