



# ECO MELT®

## Safety Data Sheet

EMERGENCY PHONE: 800-553-8011

Effective date: 06/01/2015

Print date: 5/29/2015

NFPA: Health 1, Fire 0, Reactivity 0

Page 1 of 5

### 1. IDENTIFICATION

**PRODUCT NAME:** ECO MELT®  
**CAS #:** MIXTURE

**MANUFACTURER:** OSSIAN INC., 635 SOUTH ELMWOOD AVE, DAVENPORT, IOWA 52802  
**EMERGENCY PHONE:** 800-553-8011

**PRODUCT USE:** Melting of Ice  
**USES ADVISED AGAINST:** De-icing of concrete less than one year old. De-icing of metal surfaces.

### 2. HAZARD(s) IDENTIFICATION:

#### GHS CLASSIFICATION OF MIXTURE:

<b>CONTACT HAZARD – SKIN:</b>	Category 3 – Mild skin irritation.
<b>CONTACT HAZARD – EYE:</b>	Category 2B – Mild irritant.
<b>ACUTE TOXICITY – INHALATION:</b>	No data available. Not classified.
<b>ACUTE TOXICITY – ORAL:</b>	Category 4 – Harmful if swallowed.
<b>ACUTE TOXICITY – DERMAL:</b>	Category 5 – May be harmful in contact with skin
<b>CARCINOGENICITY:</b>	Not classified as a carcinogen per GHS criteria. Not classified as a carcinogen by NTP, IARC, or OSHA

#### GHS LABELING PICTOGRAM:



#### GHS SIGNAL WORD:

**WARNING**

**HAZARD STATEMENT:** Non-toxic. No adverse health effects are anticipated with normal use of this product.

#### PRECAUTIONARY STATEMENT:

**EYE CONTACT:** Low irritant. Exposure may result in mild irritation. Can cause redness and pain.  
**INHALATION:** Low irritant – nuisance dust.  
Over exposure to dust may result in upper respiratory tract irritation.  
**SKIN CONTACT:** Low irritant. Prolonged and repeated contact with concentrate may result in slight irritation and dryness of skin to individuals with sensitive skin.  
**INGESTION:** Non-toxic in trace amounts. If ingested in large quantities seek medical attention.

**OTHER HAZARDS:** No other hazards known

### 3. COMPOSITION

**SUBSTANCE/MIXTURE:** Mixture.

<b><u>CHEMICAL NAME</u></b>	<b><u>PERCENTAGE</u></b>	<b><u>CAS NUMBER</u></b>
Sodium Chloride	> 98	007647-14-5
Polymeric Colorant	< 1	N/A
Accelerating Agent(s)	< 1	N/A

**TECHNOLOGY:** Chemical properties of accelerating agents have been withheld as a trade secret. Accelerating agents covered under U.S. Patent – additional patents may be pending.



EMERGENCY PHONE: 800-553-8011

Effective date: 06/01/2015

Print date: 5/29/2015

NFPA: Health 1, Fire 0, Reactivity 0

Page 2 of 5

#### 4. FIRST-AID MEASURES:

**FIRST AID INHALATION:** Remove to fresh air. Get medical attention for any breathing difficulty.

**FIRST AID SKIN:** Wash with soap and water. Obtain medical attention if irritation persists.

**FIRST AID EYE:** Flush gently with running water for at least 15 minutes.

**FIRST AID INGESTION:** If large amounts were swallowed give water to drink and get medical advice. Never give anything by mouth to an unconscious or convulsive person.

#### 5. FIRE-FIGHTING MEASURES:

**EXTINGUISHING MEDIA:** Use extinguishing agents appropriate for surrounding fire.

**FIRE HAZARD:** This material does not burn. Not considered to be a fire hazard.

**EXPLOSION:** Not considered to be an explosion hazard.

**PRODUCTS OF COMBUSTION:** Decomposes when heated to temperatures above 801 degrees C. May release toxic fumes of chlorine and sodium oxides.

#### 6. ACCIDENTAL RELEASE MEASURES:

**SMALL SPILLS:** Incorrect application of this product from its intended uses is not expected to be harmful to the environment.

**LARGE SPILLS:** Avoid contamination of drinking water, natural waterways, or ground water supply. Incorrect application of this product from its intended uses is not expected to be harmful to the environment.

**CLEAN UP:** Small and large spills: Contain spilled material if possible. Collect in suitable and properly labeled containers. Flush residue with plenty of water. See Section 13, Disposal Considerations, for additional information.

**ECOTOXICITY DATA:** Maybe harmful to fresh water aquatic species and to plants that are not saline tolerant.

**DISPOSAL METHOD:** Waste must be disposed of in accordance with federal, state/provincial and local environmental control regulations. Flush residue with plenty of water.

#### 7. HANDLING AND STORAGE:

**HANDLING PROCEDURES:** Avoid contact with skin and eyes, wash hands with soap and water after handling if required.

**STORAGE:** Store in cool, dry well-ventilated area, removed from acids. Ensure packaging is adequately labeled and protected from physical damage.

Incompatible with sulphuric and nitric acids, caustics, but no other critical requirements.  
Will corrode uncoated metal in storage location.



EMERGENCY PHONE: 800-553-8011

Effective date: 06/01/2015

Print date: 5/29/2015

NFPA: Health 1, Fire 0, Reactivity 0

Page 3 of 5

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION:

<b>VENTILATION CONTROLS:</b>	In general, dilution ventilation is a satisfactory health hazard control however if conditions create discomfort to the worker then a local exhaust system should be considered.
<b>PERSONAL PROTECTION:</b>	Dust goggles, long sleeves and trousers, gloves.
<b>SKIN PROTECTION:</b>	Wear protective gloves and a clean body covering clothing.
<b>EYE PROTECTION:</b>	Use dust goggles. Maintain all eyewash stations and quick drench facilities in work area.
<b>RESPIRATORY:</b>	NIOSH approved filtering face piece may be necessary

### 9. PHYSICAL AND CHEMICAL PROPERTIES:

<b>APPEARANCE (PHYSICAL STATE, COLOR, ETC)</b>	Blue colored crystalline solid
<b>ODOR:</b>	Odorless
<b>ODOR THRESHOLD:</b>	NA
<b>pH (5% SOLV/WATER):</b>	6 to 8 (Neutral)
<b>MELTING/FREEZING POINT:</b>	800.9°C (1473.6°F)
<b>INITIAL BOILING POINT:</b>	1413°C (2575.4°F)
<b>FLASH POINT:</b>	NA
<b>EVAPORATION RATE:</b>	Not applicable
<b>FLAMMABILITY:</b>	NA
<b>UPPER FLAMMABILITY LEVEL (air):</b>	NA
<b>LOWER FLAMMABILITY LEVEL (air):</b>	NA
<b>VAPOR PRESSURE:</b>	0.1 kpa (1mm hg) (at 865°C)
<b>VAPOR DENSITY (air=1):</b>	Not applicable
<b>SPECIFIC GRAVITY (water=1):</b>	2.165 (WATER = 1)
<b>SOLUBILITY:</b>	Readily soluble in water
<b>PARTITION COEFFICIENT: N-OCTANOL/WATER</b>	NA
<b>AUTO-IGNITION TEMPERATURE:</b>	NA
<b>DECOMPOSITION TEMPERATURE:</b>	NA
<b>VISCOSITY:</b>	NA

### 10. STABILITY & REACTIVITY:

<b>REACTIVITY:</b>	NA
<b>CHEMICAL STABILITY:</b>	Stable.
<b>CONDITIONS TO AVOID:</b>	None known.
<b>POSSIBILITY OF HAZAROUS REACTIONS:</b>	NA
<b>INCOMPATIBLE MATERIALS:</b>	Reactive with oxidizing agents, acids, lithium, and bromine trifluoride.
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b>	When heated to above 801 °C it emits toxic fumes of chlorine and sodium oxide.
<b>HAZARDOUS POLYMERIZATION:</b>	Will not occur.



EMERGENCY PHONE: 800-553-8011

Effective date: 06/01/2015

Print date: 5/29/2015

NFPA: Health 1, Fire 0, Reactivity 0

Page 4 of 5

### 11. TOXICOLOGICAL INFORMATION;

**ROUTES OF ENTRY:** Inhalation, Ingestion

**ACUTE:** Ingestion in large amounts (greater than 0.5 kg) can cause gastrointestinal upset and irritation of the stomach with nausea and vomiting. May affect behavior, sense organs, metabolism and cardiovascular system.

Continued exposure may produce dehydration, internal organ congestion.

The material can be irritating to the mucous membranes and upper respiratory tract.

**CHRONIC:** In severe cases Sodium Chloride can cause damage to kidneys, raise blood pressure, heartburn, osteoporosis, gastric cancers, and ventricular hypertrophy.

### 12. ECOLOGICAL INFORMATION;

The product itself and its products of degradation are not toxic.

**ENVIRONMENT:** This product is not anticipated to cause adverse effects to animal or plant life if released to the environment in small quantities. Not expected to bioaccumulate.

Solution is highly saline and large spills could potentially cause flora mortality.

### 13. DISPOSAL CONSIDERATIONS: (See Section 14 for Regulatory Information)

Reuse or recycle if possible. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Report spills if applicable. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN SDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Landfill and waste water treatment system.

### 14. TRANSPORT INFORMATION:

**UNITED STATES DOT INFORMATION:**  
This product is not regulated by D.O.T. when shipped domestically by land.

**CANADIAN TDG INFORMATION:**  
This product is not regulated by T.D.G. when shipped domestically by land.

### 15. REGULATORY INFORMATION: (Not meant to be all-inclusive- selected regulations represented)

D.O.T. PROPER SHIPPING NAME:	N/A
HAZARDOUS SUBSTANCE 49CFR CERCLA:	N/A
D.O.T. HAZARD CLASS	N/A
D.O.T. LABELS REQUIRED	N/A
D.O.T. PLACARDS REQUIRED	N/A



EMERGENCY PHONE: 800-553-8011

Effective date: 06/01/2015

Print date: 5/29/2015

NFPA: Health 1, Fire 0, Reactivity 0

Page 5 of 5

### 16. OTHER INFORMATION:

#### ADDITIONAL HEALTH DATA COMMENT:

This Safety Data Sheet contains environmental, health and toxicological information for your employees. Please make sure this information is given to them. It also contains information to help you meet community right-to-know / emergency response reporting requirements under SARA Title III and many other laws. If you resell this product, this SDS must be given to the buyer or the information incorporated in your SDS. Discard any previous edition of this SDS.

**Latest version of this SDS can be found at <http://www.OSSIAN.com>**

#### IMPORTANT:

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Ossian Inc. makes no representations as to its accuracy or sufficiency. **NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE BY OSSIAN INC. REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE.** This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal and other factors that may involve other or additional legal, environmental, safety or performance considerations, and Ossian assumes no liability whatsoever for the use of or reliance upon this information. Conditions of use are beyond Ossian's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Ossian Inc, assumes no responsibility for any injury or loss resulting from the use of the product described herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws.

OSHA Standard 29 CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, safety data sheets, training and access to written records. We request that you, and it is your legal duty to, make all information in the Safety Data Sheet available to your employees.